



# Advance Semi-auto Bio-Chemistry Analyzer

**BA-150 pro**

**A**

ccurate

**S**

table

**I**

ntelligent

**I**

nnovative



## Parameter

Incubator : Multifunctional incubator.

Test method : 1 point end, 2 point end, Kinetics, Fixed-time, Turbidity.

Test mode : Flow cell & cuvette.

Optics : 8 standard wavelengths: 340nm, 405nm, 450nm, 510nm, 546nm, 578nm, 600nm, 630nm. 2 more for optional.

Lamp house : Long-life tungsten halogen lamp, auto-sleep function.

Temperature : 25°,30°,37°C and Room Temperature, incubator Unit 370C. Flow cell capacity & optical path: 32ul, 10mm.

Resolution : 0.0001 Abs.

Photometric range : 0.0000-3.3000 Abs.

Display : 7.0" TFT LCD with touch screen, 800\*480 pixels.

Printer : Build-in thermal printer (30mm printer paper), support external printer.

CPU : ARM Cortex-AB, 800 MHz; DDRx SDRAM: 512 MB; Flash: 256 MB.

Memory : SD Card 8Gb Over 300 programs, 200000 results can be stored.

Interface : USB x 4, Ethernet Ports x1, RS232 x1.

Operational environment : Temperature: 150c~350C, Humidity: 35%~45%

Power requirement : wide power supply AC 100-240V, 50/60Hz.



**BIOSS Biotechnology GmbH**

Boekholter Weg 1a, 47638 straelen, Germany

E-mail: sales@biossbiotech.de, support@biossbiotech.de, web: www.biossbiotech.de

